PRODUCT INFORMATION

PP Interlocking Flooring Tile for

Automotive Shop and Garage use

AT94001 (AA0855) Perforated PP Interlocking

Flooring Tile


Tile Size: 333 x 333mm (13.1"x13.1") Thickness: 11.1mm (7/16") Weight: 255.15g (9 oz) FEATURES:

- Flexible Installation Options
 Use one or more Drain Tiles depending on the location
 of your floor drain to allow full access without having to
 cut a hole in your floor tiles.
- · Can customize any floor!
- Easy to assemble, no tools required!With our flooring installation is fast and easy, there is No Mess, No Glues, and No Toxic Fumes.
- Durable, Slip-Resistant, Stain-Resistant
- Supports your vehicle's weight.Drain Tile pieces quickly snap into place using the same interlocking mechanism as the floor tiles.
- Easily Repaired If Damaged Simply swap out only the damaged tiles should replacement become necessary.
- Eight standard colors to choose from. Great for garage flooring, basement flooring, play rooms, car shows, and more.
- Colors available: Blue, red, green, yellow, brown, black, grey, and white.Other colors available upon discussion.


PP Interlocking Solid Flooring Tile Slip-Resistant

AT93001 (AA0851) Round Spot Type AT92002 (AA0853) Cross Type

Tile Size: 333 x 333mm (13.1"x13.1") Thickness: 11.1mm (7/16") Weight: 340.2g (12 oz)








FEATURES:

- New Diamond Plate Style Solid Floor Tile
- · Can customize any floor!
- Easy to assemble, no tools required!
- Durable, Slip-Resistant, Stain-Resistant
- · Supports your vehicle's weight.Sound insulate construction.
- · High Quality and Professional Performance
- Eight standard colors to choose from. Great for garage
- flooring, basement flooring, play rooms, car shows, and more.With our flooring installation is fast and easy, there is
- No Mess, No Glues, and No Toxic Fumes.
- Colors available: Blue, red, green, yellow, brown, black, grey, and white.Other colors available upon discussion.
- Edging (Trim) available in White(Off-White) and Black

Can be fitted with 2mm shock and sound attenuating rubber layer.





HIMOUNT INDUSTRIAL CO., LTD. TEL: 886-2-27135577 886-2-27188886 FAX: 886-2-27152218 http://www.himount.com/ E - MAIL: himount@himount.com