

PRODUCT INFORMATION

BATTERY CHARGER

FOR YOUR INQUIRIES, PLEASE
INDICATE MODEL NO., AND
FOLLOWING
CATALOGUE NUMBER
SAT025



BATTERY CHARGER

MODEL	AT1406SX	AT1411SX
INPUT VOLTAGE	230V	230V
RATED CAPACITY	90W	125W
CHARGING VOLTAGE	12V	12V
RATED CURRENT	4.5A	7.4A
EFFECTIVE CHARGING CURRENT	6A	11A
REFERENCE CAPACITY	20-90	25-100
ISULATION CLASS	H	H
PROTECTION CLASS	IP23	IP23



BATTERY CHARGER

MODEL	AT1430S	AT1450S
INPUT VOLTAGE	230V	230V
CAPACITY	260/480W	480/730W
CHARGING VOLTAGE	12V/24V	12V/24V
CURRENT	16A	25A
BOOST CURRENT	20A	30A
REFERENCE CAPACITY	92-250	120-320
ISULATION CLASS	H	H
PROTECTION CLASS	IP23	IP23



START CHARGER

MODEL	AT14220
INPUT VOLTAGE	230V
CAPACITY	460W
CHARGING VOLTAGE	12V/24V
CURRENT	16A
EFFECTIVE CHARGING CURRENT	24A
STARTING CURRENT	130A
REFERENCE CAPACITY	70-300
ISULATION CLASS	H
PROTECTION CLASS	IP23



HIMOUNT INDUSTRIAL CO., LTD.

7TH FL. No.325, FU HSING N. ROAD.

TAIPEI, TAIWAN, R. O. C.

TEL: 886-2-27135577 886-2-27188886

FAX: 886-2-27152218

<http://www.himount.com/>

E - MAIL: himount@himount.com