

# WIRELESS INSPECTION CAMERA

FOR YOUR INQUIRIES, PLEASE  
INDICATE MODEL NO., AND FOLLOWING  
CATALOGUE NUMBER

**SAT069**  
(PAGE 1 OF 2)

## WIRELESS INSPECTION CAMERA WITH RECORDABLE MONITOR

Extend Your Hands & Eyes Even Further with Recorder!

Allows for easy visual inspection of hard- to - reach areas.

Lightweight, handheld design for easily finding.

Diagnosing and solving problems with flexible extended tube.

Useful accessories and a detachable/ mountable monitor with recording capabilities.

**AT84B035**



Attachments to fit  
the camera can meet  
different needs in  
different situations.

Hook 

Magnet 

Mirror 

Rubber ring 

3.5" LCD Monitor

 Card Up to 32 GB	 Recording Real-time	 DIGITAL ZOOM Digital ZOOM	 3.5" TFT LCD screen	 Water-proof Camera Shaft	 color Hi-Quality
--	---	--	---	--	--



20171030 HGC

HIMOUNT INDUSTRIAL CO., LTD.  
7TH FL., NO. 325, FU HSING N. ROAD, TAIPEI,  
TAIWAN  
TEL: 886-2-27135577 886-2-27188886  
FAX: 886-2-27152218  
E-MAIL: [info@himount.com](mailto:info@himount.com)  
<http://www.himount.com/>

# WIRELESS INSPECTION CAMERA

FOR YOUR INQUIRIES, PLEASE  
INDICATE MODEL NO., AND FOLLOWING  
CATALOGUE NUMBER

**SAT069**

(PAGE 2 OF 2)

## WIRELESS INSPECTION CAMERA WITH RECORDABLE MONITOR

Extend Your Hands & Eyes Even Further with Recorder!

### FEATURES

- Allows for easy surveying of small, hard-to-reach places
- Mini 9mm water-proof camera with 1m (3 ft.) flexible extended tube
- Manufactured and tested to IP67 waterproof standard
- 3.5" TFT-LCD detachable/mountable monitor, built-in rechargeable Li-battery
- Video recording capability, supports up to 32GB micro SD card
- Increase visibility with 3x zoom capability
- Adjustable brightness on lens-mounted LED light
- 3 useful accessories included: Hook, mirror and magnet
- Lightweight, handheld design, flexible and convenient to use

### PACKING LIST:

Camera x 1	USB Cable x 1
Handset x 1	Hook x 1
LCD Monitor x 1	Magnet x 1
Power Adapter x 1	Mirror x 1
Video Output Cable x 1	Rubber ring x 1

### SPECIFICATIONS

Items	Specifications
CAMERA	Imaging Sensor
	1/4-inch CMOS (OCT410S1);
	Total Pixels
	640x480
	View Angle
	45 degree
	Transmission Frequency
	2468MHz
	Minimum Illumination
	0 Lux
MONITOR	Modulation Type
	FM
	Bandwidth
	18MHz
	Power Supply
	4x AA batteries
	Unobstructed Effective Range
	10m
	Waterproof Capacity
	IP67 (Only for imager head)
MONITOR	LCD Screen Type
	3.5" TFT-LCD
	Effective Pixels
	320(R.G.B.) x 240
	Video System
	PAL/NTSC
	Transmission Frequency
	2468MHz
	Exterior Supply Voltage
	5V <sub>DC</sub>
MONITOR	Consumption Current
	500mA (Max.)
	Charge Time
	3 hours
	Work Time
	3 hours
	Picture format
	.jpg
	Video format
	.AVI
MONITOR	Built-in Li-Battery Capacity
	1500MAH/3.7V
	Memory and size
	Max. 16GB of Micro SD Card
	Picture/Video Resolution
	640x480
	Frame Rate
	30 frame/second
	Receiving Sensitivity
	≤ -85dBm
MONITOR	Operating Temperature
	-10°C~50°C/14°F~122°F
MONITOR	Operating Humidity
	15%~85%RH

### STRUCTURE



20171030 HGC

HIMOUNT INDUSTRIAL CO., LTD.  
7TH FL., NO. 325, FU HSING N. ROAD, TAIPEI,  
TAIWAN  
TEL: 886-2-27135577 886-2-27188886  
FAX: 886-2-27152218  
E-MAIL: [info@himount.com](mailto:info@himount.com)  
<http://www.himount.com/>