


FOR YOUR INQUIRIES, PLEASE INDICATE MODEL NO., AND FOLLOWING CATALOGUE NUMBER

**SAT072** 




- Hydraulic trolley jack with sturdy steel construction.
- Low profile and shallow depth for comfortable working under the vehicle.
- Raising with small pump lifts to the maximum height (75-500mm).
- Controlled releasing through the turning of the pump lever.
- Compact when disassembled with 2 piece pump lever for easy transport and storage.
- Fast lifting stroke due to two pump pistons.
- Overload protection through pressure relief valve.
- Precise hand valve for lowering.
- Pump lever with protector sponge to prevent paint scratches.
- Smooth oil and acid resistant nylon direct castors.
- Large base for safe standing.
- Integrated screw tray.



## **Optional:**





## AT20506

	Capacity			Product Size (mm)								N.W.	G.W.	Package Size	20' FCL
	Metric Tonne (CE Standard)		American Tonne (Meet ASME_PALD-2009)	A	В	с	D	Е	F	G	н	(Kg)	(Kg)	(mm)	(Pcs)
AT20505	1.50 T	2.00 T	1.70 T	70	530	150	600	830	2070	363	282	44.5	47.5	99.0x42.5x20.0	330
AT20506	2.50 T	2.50 T	2.00 T	75	425	150	500	685	1812	344	250	31.5	34.0	79.0x40.5x16.5	490
AT20507	2.75 T	3.50 T	3.00 T	95	425	150	520	720	1955	380	285	41.0	43.0	81.5x41.5x20.0	385
AT20508	3.25 T	4.00 T	3.50 T	95	425	150	520	720	1955	380	285	43.5	45.0	81.5x41.5x20.0	385



HIMOUNT INDUSTRIAL CO., LTD. 7TH FL., NO. 325, FU HSING N. ROAD, TAIPEI, TAIWAN TEL: 886-2-27135577 886-2-27188886 FAX: 886-2-27152218 E-MAIL: info@himount.com http://www.himount.com/