MOUNT

GENERAL TOOLS









AT71059 10 PCs Combination Extractor and Drill Set

Applicable:

Removes bolts and screws up to 5/8" Contents:

5. HSS Drill

Size: 5/64", 7/64", 5/32", 1/4", 19/64"

5, Screw Extractor

Size: 5/64", 7/64", 5/32", 1/4", 19/64"

AT71061 43 PCS UNF, UNC & METRIC Rethreader Kit

Contenes:

7, UNC Rethreader Dies

Size: 1/4", 5/16", 3/8", 7/16", 1/2", 9/16" & 5/8"

7, UNF Rethreader Dies

Size: 1/4", 5/16", 3/8", 7/16", 1/2", 9/16" & 5/8"

7, Metric Rethreader Dies

Size: 6 x 1.0, 8 x 1.25, 10 x 1.25, 10 x 1.5, 12 x 1.25, 12 x 1.5, 12 x 1.75 mm

6, UNC Rethreader Taps

Size: 1/4", 5/16", 3/8", 7/16", 1/2", 9/16"

6, UNF Rethreader Taps

Size: 1/4", 5/16", 3/8", 7/16", 1/2", 9/16"

7, Metric Rethreader Taps

Size: 6 x 1.0, 8 x 1.25, 10 x 1.25, 10 x 1.5, 12 x 1.25, 12 x 1.5, 12 x 1.75 mm

2, UNC and UNF Thread File

SAE Size A: 11, 12, 13, 14, 16, 18, 20, 24 Pitch SAE Size B: 9, 10, 12, 16, 20, 27, 28, 32 Pitch

1, Metric Thread File

Size: 0.75, 1,0, 1.25, 1.75, 2.0, 2.5, 3 mm

AT71063 13 PCs 3/8" & 1/2" Drive Hex Twist Socket Set

Contents:

6, 3/8" Drive Socket

Size: 8, 10, 11, 12, 13, 14 mm

5, 1/2" Drive Socket

Size: 16, 17, 18, 19, 21 mm

2, Striking Bar

AT71065 M15 x 1.5P Oil Drain Repair Kit

Applicable:

This Tool is Designed for Replacing the Damaged

Oil Drain Nut.

Choose a Suitable Tap

M14 x 1.5P Hole ---> M15 x 1.5P Tap

Work the Tap to Enlarge the Hole Thread

Place a Washer on New Oil Drain Nut and Install

the New One Into Renewed Hole

GENERAL TOOLS



AT71067 5 PCs 1/2" Drive Twist Socket Set

Applicable:

This Tool Has 6 Point and the Other Side With 6 Point Twist.
This Tool Can be Also Used While a Nut Could not be Loosen in a normal way because of rust and deformation
Contents:

4, 1/2" Drive Socket Size: 17, 19, 21, 22 mm 1, 1/2" Drive Extension Bar



AT71069 5 PCs 1/2" Drive Twist Socket Set

Contents:

4, 1/2" Drive Socket Size: 17, 19, 21, 22 mm 1, 1/2" Drive 150 mm Length Bar



AT71071 15 PCs 1/4" & 1/2" Drive Twist Socket Set

Contents:

5, 1/4" Drive Socket Size: 6, 8, 10, 11, 12 mm

8, 1/2" Drive Socket

Size: 13, 14, 15, 17, 19, 21, 24, 27mm

2, Striking Bar



AT71073 6 PCs 1/2" Drive Twist Socket Set

Contents:

5, 1/2" Drive (50 mm Length) Socket Size: 17, 19, 21, 23, 27mm

1, Striking Bar



AT71075 10 PCs Metric Flare Nut Crowfoot Wrench Set

Contents:

10, 3/8" Drive Crowfoot Wrench Size: 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 mm With a 3/8" Sq. Dr. Metal Socket Rack

