

## **FUEL SYSTEM**



# AT72P53 Hose Clamp

Applicable:

Stop the Oil Flow and avoid damaging Hoses. Adjustable for most kinds of Flexible Hoses, particularly for Brake, Fuel or Cooling system Hoses. Length 310mm, Extension Hose Clamp helps safe repair work.

Maximum Application: Ø 25.4 mm Adjust the Movable Ball and Fit the width of Hose, then screw the Adjustable Head.



Applicable:

A Large 3-1/2" Gauge with Dual Readings of 0 - 145 PSI (0-1000 KPA). Also a Low Pressure 2-1/2" Gauge for an accurate reading below 15 PSI.

All Adapters, Gauges, and Hose Assemblies Feature a Quick Coupling System for speedy and Efficient Testing connection.

The uniquely designed relief Valve Relieves the pressure and the Fuel Safely.

Also Allows Checking for sufficient Fuel Flow.

No Need for Wrenches or Pipe Dope.

The specially designed compact, neatly arranged plastic blow molded box makes storage easy. Comes complete with Instruction Manual.

The Adapter Set tests Fuel Injection systems on Vehicles on most of Models: HONDA, HYUNDAI, MAZDA, SUZUKI, TOYOTA, AUDI, BMW, MERCEDES,

PUEGOT, PORSHE, SAAB VW, VOLVO.



## AT72P57 Flow Meter Common Rail Adaptor Set

Applicable:

The purpose of this Instrument is to measure rapidly and effectively the amount of Fuel that every Injector Returns to the Deposit Tank, so that you will know if any Injector is damaged.

Direct measurement of Return Flow of the Injector. Measurement of Return Flow using External Flow Meter. Possibility of simultaneous measurement of up to 6 Injectors.

Box for Transportation and Storage is Included. Set Included 24 PCs Injector Adaptors : Apply for BOSH, SIEMENS, DENSO and DELPHI injector



### AT72P61 Gasoline Injection Pressure Test Set

Applicable:

Pressure Testing Diagnosis on a wide range of single point, Multi - Point, Mechanical and Electronic Injection System.

A Modular Range comprising  $3 \times \text{Test}$  Kits and  $2 \times \text{Workshop}$  Combination Sets, each Designed to Cover Fuel Injection System Groups.

Each Kit progressively builds up the application coverage Start with Gauge / Hose and Adptors for Test Port Entry, Increase to Encompass Single Point (TBi) and electronic Systems (EFi),

and Finally, add Mechanical Fuel Injection ( CIS ) applications.

# **FUEL SYSTEM**

### AT72P63 Diesel Injector Puller

Applicable:

Assists Removal of stubborn Bosch and Lucas Diesel Injectors

Saves time and money when Injectors are difficult to remove.

With M8, M12, M14 Adaptors



### AT72P65 21 PCs Specility Socket Set

Contents:

- 1, 17 x 78 mm Length x 12 PT.: REUAULT
- 1, 19 x 78 mm Length x 12 PT.: VW, AUDI, SEAT, MAZDA
- 1, 20 x 78 mm Length x 6 PT.: ABIERTU JAPAN
- 1, 27 x 78 mm Length x 6 PT.: ABIERTU JAPAN
- 1, 21 x 90 mm Length x 12 PT.: SEAT, AUDI, VW, SKODA, ALFA, ROMEO, MITSUBISHI
- 1, 22 x 78 mm Length x 12 PT.: SEAT, AUDI, VW,
- SKODA, OPEL 1, 22 x 110 mm Length x 12 PT.: MERCEDES, CITROEN, PEUGEOT, FORD, NISSAN, MAZDA,
- MITSUBISHI, SEAT, AUDI, VW 1, 27 x 78 mm Length x 12 PT.: SEAT, AUDI, VW, SKODA, BMW, MERCEDES, OPEL, FORD,
- NISSAN, MITSUBISHI, LINCOLN
  1, 27 x 110 mm Length x 12 PT.: CITROEN, PEUGEOT,
  SISTEN LVCAS
- 1, 28 x 78 mm Length x 12 PT.: ALFA ROMEO, FIAT, ROVER, OPEL
- 1, 30 x 78 mm Length x 12 PT.: MERCEDES
- 1, 22 x 150 mm Length x 12 PT.
- 1, 7/8" Offset Oxygen Sensor Socket
- 1, 7/8" Offset Deep Oxygen Sensor Socket
- 1, 29 x 90 mm Length x 6 PT.
- 1, 22 x 80 mm Length x 6 PT.
- 1, 22 x 90 mm Length x 6 PT.
- 1, 1" & 1-1/16" x 74 mm Length
- 1, 28 x 83 mm Length x 6 PT.
- 1, 22 mm x 6 PT. Flexible Oxygen Sensor Socket Wrench
- 1, HEX: 22mm x 110 mm Length Angled Socket: VW, AUDI, BMW, MERCEDES, FORD, OPEL, REUAULT, CITROEN, RENAULT, SEAT, SKODA, JAPANESE CARS.



Applicable:

The Tool is specifically designed for Removing Hoses. Quick and easily loosens and removes Hoses with a simple forward and backward motion.

No Need with Scresdrivers and Multi Grip Plier.



#### AT72P75 Fuel Tank Lid Remover Kit

Applicable

Carburator float remover equipped with 5 series of extensions, that include also PSA and Renault models. It fits different diameters: min. 70, max. 170 mm. Contents:

- 1, Hex. Head Auto Centering Drive with Clamping Ring
- 1, AT72P77A Jaw Set (3PCs) Height: 66mm with PVC Protection
- 1, AT72P78A Jaw Set (3PCs) Height: 34mm with PVC Protection
- 1, AT72P79A Jaw Set (3PCs) Height: 40mm
- 1, AT72P80A Jaw Set (3PCs) Height: 51.5mm
- 1, AT72P81A Jaw Set (3PCs) Height: 62mm

