



**AT71097 16 PCs 3/4" Dr. and 1" Dr.
Impact Bits and E-Sockets Set**

Applicable:

Suitable for Truck repair Engine Cylinder Head Bolts, Balance Wheels and Vibration Shocks, with easy change replaceable Bits (Bits are Fixed by a Screw and are exchangeable), Allen Key Included.

Contents:

- 9, Impact Bit, 107 mm Length,
T60, T70, T80, T90, T100, H17, H19, H22, H24
- 4, Impact Socket, 107 mm Length,
E18, E20, E22, E24
- 1, 1" Dr. Impact Socket 22 mm
- 1, 3/4" Dr. Impact Socket 22 mm
- 1, Hex Key 4 mm



AT71099 3 PCs Multi Position Pry Bar

Applicable:

Ideal for Prying Seals, Bearings, Manifolds, Oil Pans, Axles, Drive Shafts, Fuel Injectors.

Indexing Head Can Adjust 14 Fixed Angles.

Push Design for Quick Release Pry Head and easy lock to Fixed Angles

Contents:

- 3, Multi Position Pay Bar
10", 12", 15"



**AT71101 15 PCs Professional Crowfoot Wrench Set
3/8" & 1/2" Dr. Metric size: 8mm ~ 24mm**

Contents:

- 12, 3/8" Dr. Crowfoot Wrench
Size: 8, 9, 10, 11, 12, 13, 14, 15, 16,
17, 18, 19, 21, 22, 24 mm
- 3, 1/2" Dr. Crowfoot Wrench
Size: 21, 22, 24mm



**AT71103 15 PCs 3/8" Dr. Crowfoot Wrench Set
Metric size: 10mm ~ 26mm**

Contents:

- 15, 3/8" Dr. Crowfoot Wrench
Size: 10, 11, 12, 13, 14, 15, 16, 17,
18, 19, 21, 22, 23, 24, 26mm

AT71095 111 PCs Thread Repair and Workshop Kits

Applicable:

Suitable for Engines Repair and Broken Thread.
Ideal for Thread Resistance.

Contents:

25, Thread Insert M6 x 1.0 x 10.8 mm
25, Thread Insert M8 x 1.25 x 10.8 mm
25, Thread Insert M10 x 1.5 x 13.5 mm
10, Thread Insert M12 x 1.75 x 16.3 mm
5, Thread Insert M14 x 1.25 x 16.3 mm
5, Twist Drills
5, Breaking Pin Tool
5, Screw Tap
5, Installation Tool
1, Hex Key 2 mm

**AT71083 1/2" Dr. 4 Lug Spindle Nut Wrench**

Applicable:

For Use on 1982-1990 3/4 and 1 Ton GM Heavy Duty Trucks, 1985 to Current 1/2 Ton FORD F - Series and Full Size Bronco with DANA 28 Front Axle, 1985 1/2 to Current FORD F - 250 Heavy Duty Truck, 1985 1/2 to Current FORD F - 350 4 x 4, DANA 50 IFS and Model 60 Monobeam Outer Adjusting Nut.

**AT71084 1/2" Dr. 4 Lug Spindle Nut Wrench**

Applicable:

Specially Designed Socket Removes FORD Hi - Shear F 150/ 350 Rear Axles, 3/4 and 1 Ton Truck with 10-1/4" Axles, F - Super Duty Truck with Dana 80 Rear Axles. 1/2" Drive 2-3/4" O.D. 2-13/32 I.D.

**AT71085 TOYOTA Lock Nut Tool**

Applicable:

For 1995 Current Tacomas and 1996 Current T100 & 4 Runners.

Four Pin Design for quick and easy removal.

Removes Locknuts from Vehicles with new design Front Wheel Bearings.

For use with 1/2" Drive tool.

**AT71086 1/2 Ton 4 WD Wheel Bearing Locknut Tool**

Applicable:

Removes and Installs 4 Slot Front Axle Lock Nuts.

Reinforced Outer Lug Sleeve for tough applications.

Use for 1/2 Ton 4 WD Vehicles.

