



AT75T43 Wishbone Lever Tool

Applicable:

To push down the wishbone and other suspension parts, engine during the disassembly of the drive shaft, during replacing the gaiter or exchange of the wheel bearing. After loosening the ball joint the wishbone must in most cases be pushed down against the bush or stabilizer tension, in order to pull the joint from the support.

Quite of ten here problems arise:

The joint wedges against in the cone. After it was pressed down only briefly with tire lever.

The ball joint or gaiter get damaged.

The mechanic injures himselfe or damages suspension parts when the tire lever slips away with this lener tool. The work can comfortable and surely be accomplished by one person.



AT74T37 Press and Pull Sleeve Kit

Applicable:

Universal tool set for extracting and drawing in: Silent bearings, hydraulic bearings, bearing bushes, ball bearings, shaft seals, rubber bearings, etc.

Fully universal application. Ideal for different vehicles. Cars + HGVs.

Depending on requirements, the particular sleeves can also be individually reworked (e.g. recess, etc.)

Application also with workshop press + press frame.

20, Press-on sleeves

Inside: Ø 34, 36, 38, 40, 42, 44, 46, 48, 50, 52, 54, 56, 58, 60, 62, 64, 66, 68, 70, 72 mm

Outside: Ø 44, 46, 48, 50, 52, 54, 56, 58, 60, 62, 64, 66, 68, 70, 72, 74, 76, 78, 80, 82 mm

1, Universeal C-frame 245mm



AT74T391 Ball Joint-Puller Bell VIBRO-IMPACT

Applicable:

Application truck: Hino, Isuzu, Nissan, Fuso
Capacity: 15 ~ 35 Ton

Dr. 3/4", 62 mm

AT74T392 Dr. 3/4", 65 mm

AT74T06 Air Operated Stretching CV Boots Installation Tool - Lightweight Type

Applicable:

- Reduces fitting time to approximately 20 minutes
- Duragun is only 2 kg in weight
- Designed for single handed operation
- One model that covers all vehicle models
- Working pressure 4 to 8 bar
- Standard air line fitting
- Can be disconnected from the airline for fitting
- Supplied ready assembled
- Use with stretchy Universal and Duraboot CV boots
- Can be used for inner boot - simply turn boot inside out
- For joints up to 115mm

