

ENGINE, EXTERNAL

to be used for the following Brands

TWO WAY OIL FILTER WRENCH WITH TEETH

- Special design to remove and install the oil filter easily and quickly
- With pull spring to make it hold the filter easily

AT72F274A

Capacity: φ60mm - 80mm

Use with 1/2" Dr. or 21mm wrench

Leg length: 21mm



Capacity: φ80mm - 110mm

Use with 1/2" Dr. or 22mm wrench

Leg length: 30mm

AT72F274C

Capacity: φ104mm - 150mm

Use with 1/2" Dr. or 24mm wrench

Leg length: 40mm

AT72F274D

Capacity: φ104mm - 150mm

Use with 1/2" Dr. or 24mm wrench

Leg length: 64mm

AT72F274T

Capacity: φ80mm - 115mm

Use with 1/2" Dr. or 21mm wrench



AT72F321 1/2" DR. 24mm OIL FILTER WRENCH

Long type

Material: CR-MO steel

Length: 145mm

Suitable for VW DSG engine

Feature:

* Special crows foot used to remove the DSG oil filter on

VAG vehicles.

* Apparently the filter is under the battery tray and with this tool you do not have to disconnect or move the battery etc.



AT72F322 1/2" DR. 24mm OIL FILTER WRENCH

Short type

Material: CR-MO steel

Length: 101mm

Suitable for VW DSG engine

Feature:

* Special crows foot used to remove the DSG oil filter on

VAG vehicles.

* Apparently the filter is under the battery tray and with this tool you do not have to disconnect or move the battery etc.