

PRODUCT INFORMATION

FOR YOUR INQUIRIES, PLEASE
INDICATE MODEL NO., AND
FOLLOWING
CATALOGUE NUMBER
SGC011

GARDEN SUBMERSIBLE PUMP

- Plastic Housing

Operating Limits

Fluid temperature up to 35 °C

Maximum ambient temperature 40°C



** FOR CLEAN WATER

Model	GC-S250P	GC-S350P	GC-S400P	GC-S500P	GC-S750P
Supply Power	220-240V/50HZ	220-240V/50HZ	220-240V/50HZ	220-240V/50HZ	220-240V/50HZ
Input Power	250W	350W	400W	500W	750W
Max Head	8m	8m	8m	9m	9m
Max Flow	7m³/h	8m³/h	9m³/h	12m³/h	14m³/h
Max dia.of particle	5mm	5mm	5mm	5mm	5mm
Outlet	25/32mm	25/32mm	25/32mm	25/32mm	25/32mm
Cable	H05RN-F 10m	H05RN-F 10m	H05RN-F 10m	H05RN-F 10m	H05RN-F 10m



** FOR CLEAN WATER

Model	GC-S251P	GC-S351P	GC-S401P	GC-S501P	GC-S751P
Supply Power	220-240V/50HZ	220-240V/50HZ	220-240V/50HZ	220-240V/50HZ	220-240V/50HZ
Input Power	250W	350W	400W	500W	750W
Max Head	7m	8m	8m	9m	9m
Max Flow	8m³/h	8m³/h	9m³/h	12m³/h	14m³/h
Max dia.of particle	5mm	5mm	5mm	5mm	5mm
Outlet	25/32mm	25/32mm	25/32mm	25/32mm	25/32mm
Cable	H05RN-F 10m	H05RN-F 10m	H05RN-F 10m	H05RN-F 10m	H05RN-F 10m



** FOR DIRTY WATER

Model	GC-S401PW	GC-S551PW	GC-S750PW
Supply Power	220-240V/50HZ	220-240V/50HZ	220-240V/50HZ
Input Power	400W	550W	750W
Max Head	6m	6m	8m
Max Flow	9m³/h	12m³/h	13.5m³/h
Max dia.of particle	30mm	35mm	35mm
Outlet	25/32mm	25/32mm	25/32mm
Cable	H05RN-F 10m	H05RN-F 10m	H07RN-F 10m



HIMOUNT INDUSTRIAL CO., LTD.
7TH FL. No.325, FU HSING N. ROAD.
TAIPEI, TAIWAN, R. O. C.
TEL: 886-2-27135577 886-2-27188886
FAX : 886-2-27152218
<http://www.himount.com/>
E - MAIL: himount@himount.com