

PRODUCT INFORMATION

FOR YOUR INQUIRIES, PLEASE
INDICATE MODEL NO., AND
FOLLOWING
CATALOGUE NUMBER
SGC013

GARDEN SUBMERSIBLE PUMP

- Stainless Steel housing

Operating Limits

Fluid temperature up to 35 °C
Maximum ambient temperature 40°C



** FOR CLEAN WATER

Model	GC-S250S	GC-S350S	GC-S400S	GC-S500S	GC-S750S
Supply Power	220-240V/50HZ	220-240V/50HZ	220-240V/50HZ	220-240V/50HZ	220-240V/50HZ
Input Power	250W	350W	400W	500W	750W
Max Head	6m	7m	7m	7.5m	9m
Max Flow	7m ³ /h	8m ³ /h	9m ³ /h	10m ³ /h	11.5m ³ /h
Max dia.of particle	5mm	5mm	5mm	5mm	5mm
Outlet	25/32mm	25/32mm	25/32mm	25/32mm	25/32mm
Cable	H05RN-F 10m	H05RN-F 10m	H05RN-F 10m	H05RN-F 10m	H05RN-F 10m



** FOR DIRTY WATER

Model	GC-S401SW	GC-S551SW	GC-S751SW
Supply Power	220-240V/50HZ	220-240V/50HZ	220-240V/50HZ
Input Power	400W	550W	750W
Max Head	6m	6m	8m
Max Flow	9m ³ /h	10m ³ /h	14m ³ /h
Max dia.of particle	30mm	35mm	35mm
Outlet	25/32mm	25/32mm	25/32mm
Cable	H05RN-F 10m	H05RN-F 10m	H07RN-F 10m



** FOR DIRTY WATER

Model	GC-S401PSW	GC-S551PSW	GC-S751PSW
Supply Power	220-240V/50HZ	220-240V/50HZ	220-240V/50HZ
Input Power	400W	550W	750W
Max Head	6m	7m	9m
Max Flow	9m ³ /h	11m ³ /h	12m ³ /h
Max dia.of particle	30mm	35mm	35mm
Outlet	25/32mm	25/32mm	25/32mm
Cable	H05RN-F 10m	H05RN-F 10m	H07RN-F 10m



HIMOUNT INDUSTRIAL CO., LTD.
7TH FL. No.325, FU HSING N. ROAD.
TAIPEI, TAIWAN, R. O. C.
TEL: 886-2-27135577 886-2-27188886
FAX : 886-2-27152218
<http://www.himount.com/>
E-MAIL : himount@himount.com