

PRODUCT INFORMATION

FOR YOUR INQUIRIES, PLEASE
INDICATE MODEL NO., AND FOLLOWING
CATALOGUE NUMBER

SGC014

Hose / Cable Reel Series

- Mount the reel on the desired location
- Check the reel for correct operation by slowly pulling out the hose/cable. A clicking noise will be heard every half revolution of the drum
- Pull out the hose/cable until the desired length. After every click you can fix the hose/cable on that length
- When you want the hose/cable to retract, simply pull out a little further. When no click is heard, the hose/cable will retract automatically
- Never let the hose/cable retract without you controlling the speed of the retraction
- Ingenious design with excellent appearance
- Supplied with handle and swivel bracket

GC17W384



Supplied with safe locker

Water Hose Reel

Hose Length: 20M
Hose Included: 1.2M Lead-In Hose
with Connector and Simple Nozzle
Hose Material: PVC
Inlet / Outlet Size: 1/2" or 3/4"
Max. Pressure: 10Bar (140psi)
Hose I.D: 1/2"
Temperature: -5°C ~ +45°C
Outer Casing Material: PP
Dimension: 540 x 210 x 510mm
Weight: 9.1 KGs



EA02007



Cable Reel

Hose Length: 15M
Volt / AMP: 220~250V / 16A
Cable Specification: HO5W-F 3G x 1.5mm²
Cable Included: 1.5M Lead-In Supply Cable
Included with Plug and Socket
Outer Casing Material: PP
Dimension: 380 x 180 x 320mm
Weight: 5.2 KGs



PTA40614



Air Hose Reel

Hose Length: 10M
Hose Included: 1.5M Lead-In Supply Hose Included
in addition to the reel hose
Hose Material: PU
Max. Pressure: 12Bar (180psi)
Hose I.D: 1/4"
Temperature: -5°C ~ +45°C
Inlet / Outlet Size: 1/4"
Outer Casing Material: PP
Dimension: 380 x 180 x 320mm
Weight: 4.25 KGs



HIMOUNT INDUSTRIAL CO., LTD.
7TH FL. No.325, FU HSING N. ROAD.
TAIPEI, TAIWAN,
TEL: 886-2-27135577 FAX: 886-2-27152218
E - MAIL: info@himount.com
[http:// www.himount.com](http://www.himount.com)