PRODUCT INFORMATION

FOR YOUR INQUIRIES, PLEASE INDICATE MODEL NO., AND FOLLOWING CATALOGUE NUMBER

SPT215

POWER SPRAYER ACCESSORIES



Pocket Air Blow Gun

- ★ Easy grip two finger control to adjust from full volume air flow to complete shut off.
- ★ Each blow gun has a built in quick coupler nipple.

 Available with 4 different style coupler nipple.
- ★ They are used for clearing debris from a work space, drying wet surfaces.



- Knurled grip for secure handling even with oily or greasy fingers.
- It looks like a pen when clipped to your pocket.
- Recommend working pressure is 90 PSI.
 Maximum operating pressure is 150 PSI.

- Tiny size blow gun is compact and very functional.
- Rubber protection tip avoid scratching workpiece.





- ★ Pressure increments: 0.5psi/0.05bar.
- ★ LCD screen operating limits: operating temperature: -10 to 45°C. storage temperature range: -20 to 70° C.
- ★ Functional operating range: 4 to 160 psi (0 ~ 11 BAR)

★ Accuracy:

between 4 and 80 psi :± 1.0 psi (0 ~ 5.6 BAR ±0.05 BAR) between 81 and 160 psi :± 1.5 psi (5.6 ~ 11 BAR ±0.1 BAR)

★ Lithium battery life:

CR2032 will last more than 3200 cycles on/off (auto off periods of 75s) for up to 5 years.



Model No.	Material			Hose	Hose	Hose	Working	Burst	Pipe Thread
	Air Hose	Paint Hose		I.D.	O.D.	Length	Pressure	Pressure	Hose
		Inner	Outer	(mm)	(mm)	(M)	(kg/cm²)	(kg/cm²)	
PT035511K	Pu Braid	_	_	6.5	10	15	15	60	1/4" F + M fitting
	_	Nylon	Pu Braid	7.5	10.5	15	5	20	1/4" F + F fitting
PT03551A1	1	Nylon	Pu Braid	7.5	10.5	15	5	20	1/4" F + F fitting





HIMOUNT INDUSTRIAL CO., LTD. 7TH FL. No.325, FU HSING N. ROAD. TAIPEI, TAIWAN

TEL: 886-2-27135577 886-2-27188886

FAX: 886-2-27152218 http://www.himount.com/ E - MAIL: info@himount.com