

PRODUCT INFORMATION

Air Shut-Off Screwdriver Series


1/4" Hex Super Duty Full-Auto

- Dual Non Slip Grip: Comfort designed handle with micro-saw-toothed embossed surface widening towards each end to ensure grip is maintained during use
- External Torque Control: For quick and easy torque adjustment
- Dual Bearing Design: Giving smooth and efficient transmission of power, extended tool life
- Torque Operation: Automatically stops when the preset torque setting is reached
- Forward / Reverse Control: Directional switch with single handle operation
- Rear Exhaust / Handle Exhaust with Muffler

PT405P02 ~ PT405P18



Push to Start Type



External Torque Control
For quick and easy torque adjustment



Push to Start Type										
Model No.	Capacity		Torque Range		Speed rpm	Center to Outside mm	Air Cons. L/min(CFM)	Hose Size	Length mm	Weight kgs
	mm	inch	Nm	in-lb						
PT405P02	4	5/32"	1.1 ~ 2.1	9.7 ~ 18.6	1100	15.5	198 (7.0)	1/4"	187	0.43
PT405P04	3.5	9/64"	0.7 ~ 1.5	6.2 ~ 13.3	1700	15.5	198 (7.0)	1/4"	187	0.43
PT405P06	3	1/8"	0.4 ~ 1.0	3.5 ~ 8.8	2300	15.5	198 (7.0)	1/4"	187	0.43
PT405P08	5	13/64"	1.6 ~ 4.0	14.2 ~ 35.4	800	16.5	297 (10.5)	1/4"	209	0.65
PT405P10	4	5/32"	1.0 ~ 2.2	8.8 ~ 19.5	1500	16.5	297 (10.5)	1/4"	209	0.65
PT405P12	4	5/32"	1.0 ~ 1.7	8.8 ~ 15.0	2100	16.5	297 (10.5)	1/4"	209	0.65
PT405P14	5 ~ 6	13/64" ~ 15/64"	5.0 ~ 10.5	44.3 ~ 92.9	480	19.5	496 (17.5)	3/8"	240	1.0
PT405P16	5 ~ 6	13/64" ~ 15/64"	3.0 ~ 5.5	26.6 ~ 48.7	800	19.5	496 (17.5)	3/8"	240	1.0
PT405P18	4 ~ 5	5/32" ~ 13/64"	1.5 ~ 2.6	13.3 ~ 23.0	1700	19.5	496 (17.5)	3/8"	240	1.0



HIMOUNT INDUSTRIAL CO., LTD.
7TH FL. No.325, FU HSING N. ROAD.
TAIPEI, TAIWAN
TEL: 886-2-27135577 886-2-27188886
FAX: 886-2-27152218
<http://www.himount.com/>
E-MAIL: info@himount.com

PRODUCT INFORMATION

FOR YOUR INQUIRIES, PLEASE
INDICATE MODEL NO., AND FOLLOWING
CATALOGUE NUMBER

SPT256

Page 2 of 3


PT405L02 ~ PT405L12

Lever Type



PT40602 ~ PT40620

Pistol Type



External Torque Control
For quick and easy torque
adjustment



Lever Type										
Model No.	Capacity		Torque Range		Speed rpm	Center to Outside mm	Air Cons. L/min(CFM)	Hose Size	Length mm	Weight kgs
	mm	inch	Nm	in-lb						
PT405L02	3.5	5/32"	1.1 ~ 2.1	9.7 ~ 18.6	1100	15.5	198 (7.0)	1/4"	187	0.43
PT405L04	3.5	9/64"	0.7 ~ 1.5	6.2 ~ 13.3	1700	15.5	198 (7.0)	1/4"	187	0.43
PT405L06	3	1/8"	0.4 ~ 1.0	3.5 ~ 8.8	2300	15.5	198 (7.0)	1/4"	187	0.43
PT405L08	5	13/64"	1.6 ~ 4.0	14.2 ~ 35.4	800	16.5	297 (10.57)	1/4"	209	0.65
PT405L10	4	5/32"	1.0 ~ 2.2	8.8 ~ 19.5	1500	16.5	297 (10.57)	1/4"	209	0.65
PT405L12	4	5/32"	1.0 ~ 1.7	8.8 ~ 15.0	2100	16.5	297 (10.57)	1/4"	209	0.65
Pistol Type										
PT40602	3	1/8"	2.4 ~ 5.0	21.2 ~ 44.3	500	16.0	198 (7.0)	1/4"	189	0.85
PT40604	2.6	7/64"	1.1 ~ 2.1	9.7 ~ 18.6	1100	16.0	198 (7.0)	1/4"	170	0.71
PT40606	2.2	3/32"	0.7 ~ 1.5	6.2 ~ 13.3	1700	16.0	198 (7.0)	1/4"	170	0.71
PT40608	2.6	3/32"	0.4 ~ 1.0	3.5 ~ 8.8	2300	16.0	198 (7.0)	1/4"	170	0.71
PT40610	4	5/32"	1.6 ~ 4.0	14.2 ~ 35.4	1500	17.0	297 (10.5)	1/4"	175	0.87
PT40612	3.5	9/64"	1.0 ~ 2.2	8.8 ~ 19.5	800	17.0	297 (10.5)	1/4"	175	0.87
PT40614	3	1/8"	1.0 ~ 1.7	8.8 ~ 15.0	1500	17.0	297 (10.5)	1/4"	175	0.87
PT40616	5	13/64"	5.0 ~ 10.5	44.3 ~ 92.9	480	20.0	496 (17.5)	3/8"	198	1.2
PT40618	4	5/32"	3.0 ~ 5.5	26.6 ~ 48.7	800	20.0	496 (17.5)	3/8"	198	1.2
PT40620	4	5/32"	1.5 ~ 2.6	13.3 ~ 23.0	1700	20.0	496 (17.5)	3/8"	198	1.2



HIMOUNT INDUSTRIAL CO., LTD.
7TH FL. No.325, FU HSING N. ROAD.
TAIPEI, TAIWAN
TEL: 886-2-27135577 886-2-27188886
FAX: 886-2-27152218
<http://www.himount.com/>
E-MAIL: info@himount.com

PRODUCT INFORMATION

FOR YOUR INQUIRIES, PLEASE
INDICATE MODEL NO., AND FOLLOWING
CATALOGUE NUMBER

SPT256

Page 3 of 3

1/4" Hex Super Duty Air Screwdriver

Twin Dog Mechanism Type



Twin Dog Mechanism Type

PT41603



Side Exhaust

PT41606



Side Exhaust

PT41604



Side Exhaust

PT41608 for 8500 rpm

PT41610 for 7300 rpm



Handle Exhaust
with Muffler

Air Screwdriver (Twin Dog Mechanism)

Model No.	Capacity		Speed	Air Cons.	Hose Size	Length	Weight
	mm	inch	rpm	L/min(CFM)		mm	kgs
PT41602	6	1/4"	8500	71 (2.5)	3/8"	202	0.9
PT41604	6	1/4"	8500	71 (2.5)	3/8"	192	1.3
PT41606	6	1/4"	8500	71 (2.5)	3/8"	175	1.25
PT41608	6	1/4"	8500	127 (4.5)	3/8"	177	0.8
PT41610	8	5/16"	7300	65 (2.3)	3/8"	176	1.13



HIMOUNT INDUSTRIAL CO., LTD.
7TH FL. No.325, FU HSING N. ROAD.
TAIPEI, TAIWAN
TEL: 886-2-27135577 886-2-27188886
FAX: 886-2-27152218
<http://www.himount.com/>
E - MAIL: info@himount.com