

## PRODUCT INFORMATION

FOR YOUR INQUIRIES, PLEASE  
INDICATE MODEL NO., AND  
FOLLOWING  
CATALOGUE NUMBER

**SPT271**

# AUTO RETRACTABLE HOSE REEL

*With Superior Flexibility Premium Hybrid Polymer Hose  
Extremely all weather flexibility, even in subzero ( -40 ° C to + 65 ° C)*

- Max. Working Pressure: 20 BAR (300 PSI)
- Burst Pressure : 60 BAR (900 PSI)
- Zero Memory allow hose to lay flat exactly
- Superior Bend Radius
- Kink Resistant Under Pressure
- Heavy Duty Reinforced Steel Construction Reel housing
- Softness: Shore A 63±2



Model	Hose I.D.	Hose O.D.	Hose Length	Inlet/Outlet	Housing Dia.
PT0407061	8.5mm	12.5mm	10M	1/4"	27cm
PT0407063	8.5mm	12.5mm	15M	1/4"	31cm
PT0407065	8.5mm	12.5mm	20M	1/4"	33.5cm



HIMOUNT INDUSTRIAL CO., LTD.  
7TH FL. No.325, FU HSING N. ROAD.  
TAIPEI, TAIWAN.  
TEL: 886-2-27135577 FAX: 886-2-27152218  
E - MAIL : [info@himount.com](mailto:info@himount.com)  
[http:// www.himount.com](http://www.himount.com)