

AIR IMPACT WRENCH- COMPOSITE HOUSING

FOR YOUR INQUIRIES, PLEASE
INDICATE MODEL NO., AND
FOLLOWING
CATALOGUE NUMBER

SPT301


Twin Hammer / New Twin Hammer

- For strength, durability and high frequency of use there is the 3-part structure. This consists of a composite handle-housing assembly, an aluminum nose cone and an aluminum back cap. This design is available in the 1/2", 3/4" and 1" models.




• 3 positive power settings;
full power in reverse

• Ergonomic composite handle




PT37199

STANDARD




PT524300

LITE



PT524302

HIGHLY POWERFUL



PT524306 PT524308

DURABLE & POWERFUL

MODEL	SQUARE DRIVE INCH	Mechanism	FREE SPEED R. P. M.	MAX TORQUE @5SEC ft.lb(Nm)	OVERALL LENGTH INCH(mm)	AIR INLET INCH	AIR HOSE I.D	AVG.AIR CONSUMPTION cfm(L/min)	NET WEIGHT lb(kg)
PT37199	3/8"	Twin Hammer	13000	350 (475)	6.2 (157)	1/4	3/8	5.7 (161)	3.35 (1.52)
PT524300	1/2"	Twin Hammer	13000	400 (542)	6.2 (157)	1/4	3/8	5.7 (161)	3.46 (1.57)
PT524302	1/2"	Twin Hammer	9500	1000 (1356)	7.5 (190)	1/4	3/8	7.3 (207)	5.07 (2.30)
PT524303	1/2"	Twin Hammer	9000	1000 (1356)	7.8 (198)	1/4	3/8	7.0 (198)	5.42 (2.46)
PT524304	1/2"	New Twin Hammer	9000	1000 (1356)	7.8 (198)	1/4	3/8	7.0 (198)	5.56 (2.52)
PT524306	3/4"	New Twin Hammer	6000	1300 (1763)	8.7 (222)	3/8	1/2	7.3 (207)	9.24 (4.19)
PT524308	1"	New Twin Hammer	6000	1300 (1763)	8.9 (227)	3/8	1/2	7.3 (207)	9.35 (4.24)



20180103 HGC

HIMOUNT INDUSTRIAL CO., LTD.
7TH FL., NO. 325, FU HSING N. ROAD, TAIPEI, TAIWAN
TEL: 886-2-27135577 886-2-27188886
FAX: 886-2-27152218
E-MAIL: info@himount.com
<http://www.himount.com/>