

# DIGITAL TIRE INFLATOR

FOR YOUR INQUIRIES, PLEASE  
INDICATE MODEL NO., AND  
FOLLOWING  
CATALOGUE NUMBER  
**SPT314**

## 3 FUNCTION TIRE INFLATOR



**PT908529C**  
**WITH 1/4" G MALE FITTING**



**PT908529D**  
**WITH 1/4" G MALE FITTING**  
**WITH 12" DUAL CHUCK**

**FUNCTION: 0- USER ZERO**  
**1- AUTO-OFF TIME SELECTABLE**  
**2- 3 UNITS SELECTABLE**

### FEATURES :

- a. Gauge and inflator are aluminum intergrally formed.
- b. Light weight and can avoid breaking from junction.
- c. Three kinds of measure units, PSI, BAR, KPA.
- d. Battery lifetime : more than 30,000 hours / 5 years.
- e. Easy to read large LCD display.

Description	Type	PT908529C	PT908529D
Material		Aluminum	
Scale		60PSI(4.14 Bar/0.414Mpa)	200PSI (14Bar/1.4MPa)
Display resolution		±2%FS ± 1 digit	
Hose length		30cm	85cm
Dimensions		200L* 65W * 100H mm	
Weight		470 g	680 g
Supply pressure max.		240PSI / 16.6 Bar / 1.66 Mpa	
Supply voltage		DC 3V ( CR2032)	
Working temperature		-5 ~ + 50 °C ( 14 ~ 122°F )	
Inflation speed		490 L/min @ 145 PSI	



20180725 HGC



ID 0000062294

HIMOUNT INDUSTRIAL CO., LTD.  
7TH FL. No.325, FU HSING N. ROAD.  
TAIPEI, TAIWAN  
TEL: 886-2-27135577 886-2-27188886  
FAX : 886-2-27152218  
<http://www.himount.com/>  
E - MAIL: [info@himount.com](mailto:info@himount.com)