**SPT318** 

# Heavy Duty Ratchet Wrench



- For added strength



#### TORQUE

- 85 ft-lb torque output to remove stubborn fasteners

## EXHAUST DEFLECTOR

SELECTOR KNOB

- For easy direction change

- 360° Exhaust to direct air away from user

#### RATCHET HOUSING

 Heat-treated ratchet housing for durability

#### RPM

- 280 RPM fast removal and installation of fasteners

#### **CUSHION GRIP**

 Over-molded grip for added comfort and reduce vibration

### TRIGGER KNOB

- Tip valve style trigger for precise control

Item No.	<b>Square Drive</b>	Speed	Working	Torque	Max.	Torque	Avg. Air Consumption	Length
PT389135	3/8"	280 rpm	75 ft-lb	102 Nm	85 ft-lb	115 Nm	4.5 cfm 127 i/min	12 in 305 mm
PT389137	1/2"	280 rpm	75 ft-lb	102 Nm	85 ft-lb	115 Nm	4.5 cfm 127 i/min	12 in 305 mm



7TH FL. No.325, FU HSING N. ROAD. TAIPEI, TAIWAN TEL: 886-2-27135577 886-2-27188886

FAX: 886-2-27152218 http://www.himount.com/ E - MAIL: info@himount.com