

# PUSH BUTTON SAFETY COUPLER

CATALOGUE NUMBER  
SPT330

Light Weight, Anti-Rust, Safety

## Technical Data

Double-click pushbutton safety coupler relieves air pressure for safe disconnect

Reduces the chance of an accidental air line disconnect.

Uses double click to engage properly. First click locks coupler and plug; second click engages air pressure.

When disconnecting, first click will relieve air pressure; second click allows coupler and plug to be safely disengaged.












Reduces the risk of possible injury or damage due to accidental air line disconnect.

## Material

Nylon + Fiberglass composite

scan to watch the operation video:  
<https://youtu.be/BLstOqcO6Mw>



Safety Quick Couplings	Profiles	Model No.	Connection	Thread	Flow at 6.2 BAR l / min
	<p>European</p> 	QABF2E02	1/4" Female	PT	1048
		QABF3E02	3/8" Female	PT	1076
		QABM2E02	1/4" Male	PT	963
		QABM3E02	3/8" Male	PT	963
	<p>Universal for A &amp; B</p> <p>A: Milton</p> <p>B: Tri Flate Profile</p> 	QABF2M02	1/4" Female	NPT	991
		QABF3M02	3/8" Female	NPT	1020
		QABM2M02	1/4" Male	NPT	963
		QABM3M02	3/8" Male	NPT	963
	<p>Japanese</p> 	QABF2N01	1/4" Female	PT	1048
		QABF3N01	3/8" Female	PT	1076
		QABM2N01	1/4" Male	PT	963
		QABM3N01	3/8" Male	PT	963



20190905 / HGC



HIMOUNT INDUSTRIAL CO., LTD.

7TH FL. No.325, FU HSING N. ROAD.  
TAIPEI, TAIWAN

TEL: 886-2-27135577 FAX: 886-2-27152218

<http://www.himount.com>

E - MAIL: [info@himount.com](mailto:info@himount.com)