

Wall Mounted Tire Inflator

FOR YOUR INQUIRIES, PLEASE
INDICATE MODEL NO., AND
FOLLOWING
CATALOGUE NUMBER
SPT356 - Page 1

<Feathers>

Reliable, tough and easy to use, Automatic Tire Inflators are designed to inflate tires of cars, trucks, tractors, military vehicles and planes.

Built in multiple functions, the automatic tire inflator will automatically start inflation or deflation once it is connected to the tire valve to precisely reach the selected pressure.

Strong IP56 aluminum die cast housing is suitable for no matter indoor work shops or outdoor repair station, and the they are Nitrogen compatible.

With CE certificate.

PT908670 - Wall Mounted Tire Inflator



- * Inflate or deflate your tires automatically up to 10 bar / 145 psi.
- * 7.6 m air hose to easily reach all tires on the vehicle.
- * Only 2 min. 20 sec. to inflate a 11R22.5 tire from 0 to 6.89 bar / 100 psi.
- * Loud audible signal warns you that the tire has reached the set pressure.
- * 4 measurement units (psi, bar, kPa, kg/cm²), Over pressure setting(OPS), LCD screen & backlight.

Reader units	Digital display
Chuck type	Clip on
Chuck style	Single straight
Scale:	0.5-10bar 7-145psi 50-1000kpa 0.5-10kg/cm ²
Display on/off default pressure	2 bar
Inlet size	6.35mm(1/4")
Hose length	7.6m
Dimensions	310*300*220 mm
Weight	14 lb / 6 kg
Accuracy	±2psi Exceeds EEC/86/217 COMPLIANCE
Operation	Auto inflate and deflate
Supply pessure max	10.5bar 152psi 1050kpa 10.5kg/cm ²
Advised application	Industrial, workshops
Debit:	Max 92 CFM - 2600L/min
Supply voltage	AC110-240V/50-60Hz

PT908672 - High Flow Wall Mounted Tire Inflator



- * Inflate or deflate your tires automatically up to 10 bar / 145 psi.
- * 2 m air hose x 4pcs to inflate or deflate 4 tires at the same time.
- * Only 4 min. 12 sec. to inflate 4 x 11R22.5 tires from 0 to 6.89 bar / 100 psi.
- * Loud audible signal warns you that the tire has reached the set pressure.
- * 4 measurement units (psi, bar, kPa, kg/cm²), Over pressure setting(OPS), LCD screen & backlight.

Reader units	Digital display
Chuck type	Clip on
Chuck style	Single straight
Scale:	0.5-10bar 7-145psi 50-1000kpa 0.5-10kg/cm ²
Display on/off default pressure	2 bar
Inlet size	6.35mm(1/4")
Hose length	2 m * 4
Dimensions	310*300*220 mm
Weight	Body 5kg; Hose Ass 6kg
Accuracy	±2psi Exceeds EEC/86/217 COMPLIANCE
Operation	Auto inflate and deflate
Supply pessure max	10.5bar 152psi 1050kpa 10.5kg/cm ²
Advised application	Industrial, workshops
Debit:	Max 92 CFM - 2600L/min
Supply voltage	AC110-240V/50-60Hz



1111121 - YJD



HIMOUNT INDUSTRIAL CO., LTD.
7TH FL., NO. 325, FU HSING N. ROAD, TAIPEI, TAIWAN
TEL: 886-2-27135577 886-2-27188886
FAX: 886-2-27152218
E-MAIL: info@himount.com
<http://www.himount.com/>

Wall Mounted Tire Inflator

FOR YOUR INQUIRIES, PLEASE
INDICATE MODEL NO., AND
FOLLOWING
CATALOGUE NUMBER
SPT356 - Page 2

PT908674 - High Pressure Wall Mounted Tire Inflator



Reader units	Digital display
Chuck type	Clip on
Chuck style	Single straight
Scale:	0.5-13bar 7-188psi 50-1300kpa 0.5-13kg/cm ²
Display on/off default pressure	2 bar
Inlet size	6.35mm(1/4")
Hose length	7.6m
Dimensions	310*300*220 mm
Weight	14 lb / 6 kg
Accuracy	±2psi Exceeds EEC/86/217 COMPLIANCE
Operation	Auto inflate and deflate
Supply pressure max	16bar 232psi 1600kpa 16kg/cm ²
Advised application	Industrial, workshops
Debit:	Max 92 CFM - 2600L/min @ 232 psi
Supply voltage	AC110-240V/50-60Hz

- * Inflate your high-pressure tires automatically up to 232 psi/16 bar.
- * 7.6 m air hose to easily reach all tires on the vehicle.
- * Only 2 min. 20 sec. to inflate a 11R22.5 tire from 0 to 6.89 bar / 100 psi.
- * Loud audible signal warns you that the tyre has reached the set pressure.
- * 4 measurement units (psi, bar, kPa, kg/cm²), Over pressure setting(OPS), LCD screen & backlight.

PT908676 - N2P Wall Mounted Tire Inflator



Reader units	Digital display
Chuck type	Clip on
Chuck style	Single straight
Scale:	0.5-10bar 7-145psi 50-1000kpa 0.5-10kgf
Display on/off default pressure	2.00 bar
Inlet size	6.35mm(1/4")
Hose length	7.6m
Dimensions	310*300*220 mm
Weight	14 lb / 6 kg
Accuracy	±2psi Exceeds EEC/86/217 COMPLIANCE
Operation	Auto inflate and deflate
Supply pressure max	10.5bar 152psi 1050kpa 10.5kg/cm ²
Advised application	Industrial, workshops
Debit:	Max 92 CFM - 2600L/min
Supply voltage	AC110-240V/50-60Hz

- * Inflate or deflate your tires automatically up to 10 bar / 145 psi.
- * 7.6 m air hose to easily reach all tires on the vehicle.
- * Only 2 min. 20 sec. to inflate a 11R22.5 tire from 0 to 6.89 bar / 100 psi.
- * Loud audible signal warns you that the tire has reached the set pressure.
- * 4 measurement units (psi, bar, kPa, kg/cm²), Over pressure setting(OPS), LCD screen & backlight.
- * Nitrogen purge and fill cycle (N2P).



1111121 - VJD



HIMOUNT INDUSTRIAL CO., LTD.
7TH FL., NO. 325, FU HSING N. ROAD, TAIPEI, TAIWAN
TEL: 886-2-27135577 886-2-27188886
FAX: 886-2-27152218
E-MAIL: info@himount.com
<http://www.himount.com/>