

PRODUCT INFORMATION

Digital Torque Wrench

FOR YOUR INQUIRIES, PLEASE
INDICATE MODEL NO., AND FOLLOWING
CATALOGUE NUMBER
STS155
(Page 1 of 2)

- **Quick, Accurate Torqing for Every Nut, Bolt and Fastener**
- **Quality Control and Assurance with Data Recording**
- **Everyday Reliability with Robust Build and High Quality Components**
- **Reduced Downtime and Maintenance with Online Calibration**
- **Getting Properly Torqued Fasteners is Quickly and Easy with up to $\pm 2\%$ Accuracy.**

Interchangeable Head

- Head interchangeable.
- Accuracy $\pm 2\%$.
- Multiple functions including torque setting, unit setting, mode setting, date clear, date output and online calibration.
- 9 pre-settable target torque values
- Functions in both clockwise and anticlockwise directions.
- LCD display showing N-m, ft-lb, in-lb and kg-cm measurements.
- Audible and visible torque confirmation by buzzer and 2 LED display.
- Data memory size 50 or 250 optional.
- 250 data memory points with PC connectivity for data download (software included).

Fixed Head

- Standard functions including torque setting, unit setting, mode setting and online calibration.
- Accuracy $\pm 3\%$.
- Functions in both clockwise and anticlockwise directions.
- LCD display showing N-m, ft-lb, in-lb and kg-cm measurements.
- Audible and visible torque confirmation by means of buzzer and 12 LED display.
- Easy to set-up per application.



When approaching the target torque, the green lights will illuminate (a warning signal).
When the target torque has been reached, the red lights will illuminate (a stop signal).

Item No.	Square Driver	Overall Length	Accuracy	Measured Torque Range		Gear Teeth	Operating Temperature	Bright LED
				N-m	ft-lb			
Interchangeable Head								
TS06220	1/4"	390	$\pm 2\%$	1.5 ~ 30	1.11 ~ 22.12	36	-10 ~ 60 °C	2 LEDs Red+Green
TS06230	3/8"	410	$\pm 2\%$	6.8 ~ 135	5 ~ 99.5	36	-10 ~ 60 °C	
TS06240	1/2"	410	$\pm 2\%$	6.8 ~ 135	5 ~ 99.5	36	-10 ~ 60 °C	
TS06242	1/2"	545	$\pm 2\%$	10 ~ 200	7.4 ~ 147.5	36	-10 ~ 60 °C	
TS06244	1/2"	640	$\pm 2\%$	17 ~ 340	12.5 ~ 250.7	36	-10 ~ 60 °C	
Fixed Head								
TS06020	1/4"	390	$\pm 3\%$	1.5 ~ 30	1.11 ~ 22.12	36	-10 ~ 60 °C	12 LEDs 4 Red 8 Green
TS06030	3/8"	415	$\pm 3\%$	6.8 ~ 135	5 ~ 99.5	36	-10 ~ 60 °C	
TS06040	1/2"	415	$\pm 3\%$	6.8 ~ 135	5 ~ 99.5	36	-10 ~ 60 °C	
TS06042	1/2"	530	$\pm 3\%$	10 ~ 200	7.4 ~ 147.5	36	-10 ~ 60 °C	
TS06044	1/2"	640	$\pm 3\%$	17 ~ 340	12.5 ~ 250.7	36	-10 ~ 60 °C	



HIMOUNT INDUSTRIAL CO., LTD.
7TH FL. No.325, FU HSING N. ROAD.
TAIPEI, TAIWAN, R. O. C.
TEL: 886-2-27135577 886-2-27188886
FAX: 886-2-27152218
<http://www.himount.com/>
E - MAIL: himount@himount.com

PRODUCT INFORMATION

Digital Torque Wrench

FOR YOUR INQUIRIES, PLEASE
INDICATE MODEL NO., AND FOLLOWING
CATALOGUE NUMBER
STS155
(Page 2 of 2)



- LCD display avoid sight misreading caused on mechanic torque wrench.
- Unit transfers between Nm, lb-ft and lb-inch automaticly.
- Bright LED and loud Buzzer can be easily recognized during work.
- Square handle with non-slip rubber provides comfortable and ergonomic grip.



	Flexible Torque Wrench		400mm Torque Wrench		570mm Torque Wrench	
	3/8"	1/2"	3/8"	1/2"	3/8"	1/2"
Art. No.	TS35001	TS35000	TS60038	TS60041	TS60039	TS60042
Length	400mm	400mm	400mm	400mm	570mm	570mm
Ratch Head	48 teeth	48 teeth	45 teeth	45 teeth	45 teeth	45 teeth
Torque(N-m)	10 - 135	10 - 135	10 - 135	10 - 135	20 - 200	20 - 200
Battery	9V x 1pc	9V x 1pc	9V x 1pc	9V x 1pc	9V x 1pc	9V x 1pc
Packing	Blow case	Blow case	Blow case	Blow case	Blow case	Blow case
Weight	1.2 kgs	1.2 kgs	1.2 kgs	1.2 kgs	1.6 kgs	1.6 kgs



HIMOUNT INDUSTRIAL CO., LTD.
7TH FL. No.325, FU HSING N. ROAD.
TAIPEI, TAIWAN, R. O. C.
TEL: 886-2-27135577 886-2-27188886
FAX : 886-2-27152218
<http://www.himount.com/>
E - MAIL: himount@himount.com