

PRODUCT INFORMATION

FOR YOUR INQUIRIES, PLEASE
INDICATE MODEL NO., AND FOLLOWING
CATALOGUE NUMBER

STS166

Page 1 of 3

Torque Wrench Series

Adjustable Torque Series

Mini Torque Wrench

- Industrial application
- Tolerance of torque $\pm 3\%$
- Quick release design
- Quality meets DIN ISO 6789 and ASME B107.14
- CW/CCW direction



Mini Torque Wrench



Mini Interchangeable
Torque Wrench

Mini Torque Wrench

Model No.	Square Drive Size	Teeth	Torque Range (Nm/in-lb)	Graduation	Length (mm)	Weight (g)
TS223271	1/4"	64T	1 ~ 6 / 11.1 ~ 50.9	0.05	210	288
TS223281	1/4"	64T	3 ~ 15 / 31 ~ 128	0.1	210	288
TS223251	1/4"	64T	5 ~ 25 / 53 ~ 212	0.2	248	325
TS223242	3/8"	64T	1 ~ 6 / 11.1 ~ 50.9	0.05	210	288
TS22324	3/8"	64T	3 ~ 15 / 31 ~ 128	0.1	210	288
TS223241	3/8"	64T	5 ~ 25 / 53 ~ 212	0.2	248	325

Mini Interchangeable Torque Wrench

TS223262	9 x 12mm	NIL	1 ~ 6 / 11.1 ~ 50.9	0.05	197	257
TS22326	9 x 12mm	NIL	3 ~ 15 / 31 ~ 128	0.1	197	257
TS223261	9 x 12mm	NIL	5 ~ 25 / 53 ~ 212	0.2	227	297


Interchangeable Insert Tools (Can Be Chosen)



Open Ended Type
Size: 7mm ~ 36mm (or 1/4" ~ 3/4")
Full Range for Choice



Ring Type
Size: 7mm ~ 22mm (or 1/4" ~ 7/8")
Full Range for Choice



Ratchet Type
Size: 1/4", 3/8", 1/2" Drive

TS22325

Mini Torque Wrench Kit

Contents:

- 1, 1/4" Mini Torque Wrench 5 ~ 25Nm
- 7, 1/4" Bit Socket
Size: H3, 4, 5, 6, 8, 10, T25

Also Available:

TS22327

For 1/4" Mini Torque Wrench 1 ~ 6Nm Kit

TS22328

For 1/4" Mini Torque Wrench 3 ~ 15Nm Kit



HIMOUNT INDUSTRIAL CO., LTD.
7TH FL. No.325, FU HSING N. ROAD.
TAIPEI, TAIWAN
TEL: 886-2-27135577 886-2-27188886
FAX: 886-2-27152218
<http://www.himount.com/>
E - MAIL: info@himount.com

PRODUCT INFORMATION

FOR YOUR INQUIRIES, PLEASE
INDICATE MODEL NO., AND FOLLOWING
CATALOGUE NUMBER

STS166

Page 2 of 3

Fixed Torque Series

- 1/2" Drive
- Diversifield products can widely apply
- Easy and flexible operation of design
- Comfortable, durable handle
- Audible "Click" when torque reached
- Accuracy: $\pm 4\%$
- Certified by: DIN ISO 6789, BS26789 and ASME B107.14



Torque Wrench



Contents:

- 5, Fixed Torque Wrench
- 5, 1/2" Dr. Wheel Nut Impact Socket
17, 19, 21mm, 13/16", 7/8"
- 5, Torque Extension Bar
90Nm/65ft-lb, 110Nm/80ft-lb,
135Nm/100ft-lb, 160Nm/120ft-lb,
190Nm/140ft-lb,



Contents:

- 5, Fixed Torque Wrench
- 5, 1/2" Dr. Impact Deep Socket L: 75mm
15, 17, 19, 21, 22mm
- 1, Extension Bar L: 75mm
- 1, Foldable Cross Handle Socket Wrench

Model No.	Square Driver	Range	Length mm	Weight kgs	Color
TS223141	1/2" Dr.	88 Nm / 65 ft-lb	580	1.6	
TS223142	1/2" Dr.	108 Nm / 80 ft-lb	580	1.6	
TS223143	1/2" Dr.	135 Nm / 100 ft-lb	580	1.6	
TS223144	1/2" Dr.	163 Nm / 120 ft-lb	580	1.6	
TS223145	1/2" Dr.	190 Nm / 140 ft-lb	580	1.6	

L-Preset Torque Wrench

- 1/2" Drive
- 105° Angle in direction
- Accuracy: $\pm 4\%$
- Audible "Click" when torque reached
- Quality meets DIN ISO 6789 and ASME B107.14



Model No.	Square Driver	Range	Length mm	Weight kgs	Color
TS222941	1/2" Dr.	90 Nm / 66.3 ft-lb	428	0.824	
TS222942	1/2" Dr.	100 Nm / 73.7 ft-lb	428	0.824	
TS222943	1/2" Dr.	110 Nm / 81.0 ft-lb	428	0.824	
TS222944	1/2" Dr.	120 Nm / 88.4 ft-lb	428	0.824	
TS222945	1/2" Dr.	130 Nm / 95.8 ft-lb	428	0.824	



HIMOUNT INDUSTRIAL CO., LTD.
7TH FL. No.325, FU HSING N. ROAD.
TAIPEI, TAIWAN
TEL: 886-2-27135577 886-2-27188886
FAX : 886-2-27152218
<http://www.himount.com/>
E - MAIL: info@himount.com

PRODUCT INFORMATION

FOR YOUR INQUIRIES, PLEASE
INDICATE MODEL NO., AND FOLLOWING
CATALOGUE NUMBER

STS166
Page 3 of 3

Preset Torque Limiter

- Tolerance of torque $\pm 6\%$
- Rotary clutch mechanism when derired torque reached
- For fastening torque in CW/CCW direction
- Light-weight easy to use
- The customization for the torque setting
- Quality meets DIN 6789 and DIN 3120
- For low torque applications i.e. motorcycle or bicycle production lines

Model No.	Input	Output	Torque Range	Length	Weight
				mm	g
TS222131	3/8" Dr.	1/4" Hex Dr.	0.5 ~ 5 Nm	75	91
TS222132	3/8" Dr.	1/4" Hex Dr.	5 ~ 10 Nm	75	91
TS222133	3/8" Dr.	1/4" Hex Dr.	4.5 ~ 40 Nm	75	91
TS222134	3/8" Dr.	1/4" Hex Dr.	45 ~ 85 Nm	75	91
TS222135	3/8" Dr.	3/8" Dr.	0.5 ~ 5 Nm	75	91
TS222136	3/8" Dr.	3/8" Dr.	5 ~ 10 Nm	75	91
TS222137	3/8" Dr.	3/8" Dr.	4.5 ~ 40 Nm	75	91
TS222138	3/8" Dr.	3/8" Dr.	45 ~ 85 Nm	75	91



Torque Protractor

- 360° angle scale-clearly marked in 2° increments, and in intervals of 10° and 30°
- Indicator etched on clear plastic plate-protects angle scale from dirt and grease
- Adjustable arm keeps angle scale stationary
- Arm has two lengths for additional flexibility in placement against components
- Tough composite dial and rotating index allow operator to accurately tighten fixing to manufacturers exact standard



TS22232

Square Drive: 1/2" x 1/2"
Weight: 160g



TS22234

Square Drive: 1/2" x 1/2"
Weight: 360g
Square Drive: 3/4" x 3/4"
Weight: 620g



TS22235

Square Drive: 1/2" x 1/2"
Weight: 255g



HIMOUNT INDUSTRIAL CO., LTD.
7TH FL. No.325, FU HSING N. ROAD.
TAIPEI, TAIWAN
TEL: 886-2-27135577 886-2-27188886
FAX : 886-2-27152218
<http://www.himount.com/>
E - MAIL: info@himount.com