Metric + Sal anti-Sup rattleting wrenth

FOR YOUR INQUIRIES, PLEASE INDICATE MODEL NO., AND FOLLOWING CATALOGUE NUMBER

STS239

ANTI-SLIP COMBINATION RATCHET WRENCH

Model	Size	A	ФС	OVERALL LENGTH
	mm(inch)	mm	mm	mm
TS243K108	8(5/16)	18.2	17.4	136
TS243K109	9	20.5	19.2	142
TS243K110	10(3/8)	22.5	20.9	160
TS243K111	11(7/16)	24	22.6	168
TS243K112	12	26.2	24.2	174
TS243K113	13(1/2)	27.3	26.6	180
TS243K114	14(9/16)	30.9	27.6	190
TS243K115	15	32.4	29	200
TS243K116	16(5/8)	34.1	30.8	215
TS243K117	17(11/16)	37.9	33.3	230
TS243K118	18	39.4	33.8	240
TS243K119	19(3/4)	40.7	35.6	248
TS243K121	21(13/16)	45	41.3	285
TS243K122	22(7/8)	45	41.3	285
TS243K124	24(15/16)	51.6	46.8	325
TS243K125	25(1)	51.6	46.8	325





4-IN-1 OPEN ENDS RATCHET WRENCH

Model	SIZE	SAE	WIDTH OPEN	OVERALL LENGTH
	mm	Inch	mm	mm
TS243J108	8 x 10	5/16" x 3/8"	20.3 x 22.7	150
TS243J110	10 x 11	3/8" x 7/16"	23.7 x 26.1	170
TS243J113	13 x 14	1/2" x 9/16"	29.9 x 32.0	190
TS243J114	14 x 15	9/16" x 5/8"	34.5 x 35.3	210
TS243J117	17 x 19	11/16" x 3/4"	38.7 x 42.1	228



Feathers:

- 1. Combine Metric & SAE in One Wrench.
- 2. Work On 80% Rounded Off Fastener.
- 3. Ratchet Design for Box End and Open End.
- 4. Special Design Doesn't Round Fasteners.
- 5. 100T Gear and 3.6° Swing Arc for Box End.
- 6. Torque Meet ANSI Standard.
- 7. Endurance Torque (Life Cycle) Exceeds 30,000 Strokes at 33% ANSI Standard.
- 8. Pass ANSI Drop Test: Dropped On Concrete Twelve Times from Height of 183cm(6ft).





