

PRODUCT INFORMATION

15" Variable Speed Drill Press with Electronic Digital Readout *For industrial market*

FOR YOUR INQUIRIES, PLEASE
INDICATE MODEL NO., AND FOLLOWING
CATALOGUE NUMBER

STT015



Model No.
TD-15VS



Standard Features:

- Spindle runs from 400-5000 RPM, instant speed selection by one simple handwheel
- **Electronic Digital readout shows spindle RPM immediately**
- Full bearing support for maximum spindle stiffness
- 152 mm stroke: for deep hole applications
- Larger quill for attaining greater accuracy (Dia. 57 mm)
- Larger production worktable provides more support and room for operator's needs
- 76.2 mm column forms the backbone of the system, gains more rigidity
- Bench model available
- **With chuck guard (CE model)**
- **With Magnetic Switch (CE model)**

Specifications:

Floor Model:

Table working surface:	317 mm x 368 mm
T-slot:	12.7 mm
Spindle to table:	1040 mm
Overall height:	1715 mm
Weight:	130 kgs

Bench Model:

Table working surface:	269 mm x 314 mm
Spindle to base:	279 mm (max) 152 mm (min)
Overall height:	927 mm
Weight:	110 kgs.

Capacity, cast iron:	Up to 15.9 mm
Capacity, steel:	Up to 12.7 mm
Column diameter:	76.2 mm
Drill to center:	380 mm
Quill Diameter:	57 mm
Quill travel:	152 mm
Spindle taper:	#2 MT; 16 mm keyed chuck with #2 MT arbor
Spindle speeds, vari-speed:	400-5000 RPM



HIMOUNT INDUSTRIAL CO., LTD.

7TH FL. No.325, FU HSING N. ROAD.

TAIPEI, TAIWAN, R. O. C.

TEL : 886-2-27135577 886-2-27188886

FAX : 886-2-27152218

E-Mail : himount@himount.com