PRODUCT INFORMATION

CATALOGUE NUMBER **STT017**

20" Electronic Variable Speed **Drill Press** with Electronic Digital Readout



Model No. TD-20AC



Standard Features:

- Infinitely variable speeds 65 to 2000
- **Electronic Digital readout shows** spindle RPM immediately
- High/Low gear box drive system
- Latest AC Inverter variable speed technology
- High torque at all speeds both forward and reverse
- Continuous speed adjustment while in operation
- Forward and reverse for tapping standard
- Emergency stop button
- Front or side operated rack worm gear raiser
- Machine T-slotted base with built-in coolant tank for optional coolant system

With chuck guard

Specifications:

Capacity, cast iron: 38 mm Capacity, steel: 34.9 mm Column diameter: 114 mm Max. spindle to column surface: 265 mm Quill Diameter: 57 mm Quill travel: 152 mm Spindle taper: #3 MT Spindle speeds, vari-speed: 65-2000 RPM Motor: 2 HP, 1 ph, or 3 ph AC Inverter

Table working surface: 460 mm x 374 mm Table travel: 822 mm

822 mm Max. spindle to table:

387 mm x 306 mm Base working surface:

Table/Base T-slot: 15.8 mm

930/685/2089 mm Machine L/W/H:

Net Weight: 319 kgs Shipping Weight: 359 kgs



HIMOUNT INDUSTRIAL CO., LTD.

7TH FL. No.325, FU HSING N. ROAD.

TAIPEI, TAIWAN, R. O. C.

TEL: 886-2-27135577 FAX: 886-2-27152218 886-2-27188886

E-Mail: himount@himount.com