

HIMOUNT INDUSTRIAL CO., LTD



7th FL. NO. 325, FU HSIN N. RD.
TAIPEI, TAIWAN, R.O.C.

TEL: 886-2-27135577
FAX : 886-2-27152218
EMAIL:
himount@himount.com

PRODUCT INFORMATION

NO. STT023

Dec. 17, 2002

TO:

Description : **Gear Head Drill/Mill (32mm Capacity)**
Model No. : **TT-26210** with Square Table
TT-26212 with Cross Table
TT-26220 with Square Table, Spindle Power Feed
TT-26218 with Cross Table, Spindle Power Feed

Specification :

Capacity : Drilling : 32mm in Cast Iron
32mm in Mild Steel
Face Mill : 100mm in Cast Iron
End Mill : 20mm in Cast Iron
Tapping : 16mm in Cast Iron

Motor : 1 HP, 3 phase

Spindle Speed : 50 - 1,250 RPM
50 - 2,500 RPM
(optional, with 2-speed motor)

Spindle Taper : MT#3

Spindle Stroke : 130mm

Swing : 520mm

Spindle Power Feed : 0.12, 0.18, 0.25mm per/rev.
(TT-26220, TT-26218)

Square Table : 540 x 470mm

Cross Table : 585 x 190mm

Longitudinal Travel : 340mm (TT-26212, TT-26218)

Cross Travel : 180mm (TT-26212, TT-26218)

Column Diameter : 115m

W/O coolant system



TT-26210, TT-26212

TT-26220, TT-26218

Packaging:

Each machine packed in a crate 839 x 737 x 1143mm

TT-26210, TT-26212 : 270kgs/300kgs, 40.4 CUFT

TT-26220 TT-26218 : 280kgs/310kgs, 40.4 CUFT

20' Containerload : 21 machines

Business Terms

Port : FOB Taiwan

Country Of Origin : Taiwan

Mini Order Q'ty :

Delivery (Days) : 40 days after order confirmation

FOB Price (US\$) :