

# PRODUCT INFORMATION

## ***Hollow Chisel Morticer***

Chisel Capacity : Up to 16mm

For Woodworking Applications

Model No. **TT-916**



FOR YOUR INQUIRIES, PLEASE  
INDICATE MODEL NO., AND FOLLOWING  
CATALOGUE NUMBER

**STT028**



### Standard Features:

- **Powerful Morticing Capability** – the chuck is directly driven by a 1/2 HP motor for powerful morticing operations. The chisel capacity is up to 16mm.
- **Minimum Operation Fatigue** - The long operating lever controls the morticing head downfeed. It incorporates a correct counter-balance weight enclosed within the work bench for smooth morticing operations and minimum fatigue
- **Precision Head Downfeed** – The morticing head is maneuvered on a dovetail slide way for precision downfeeding. The bit is driven by a 1/2 HP motor with a totally enclosed fan ventilation system
- **Depth Stop** – A depth stop is provided for accurate morticing control
- **Air Spring** – An air spring instead of regular spring is provided for a safe downfeeding, the lever would not bounce up.

### Specifications:

- Motor : 1/2 HP
- Chisel Capacity : 6 – 16mm
- Max Chisel Stroke : 153mm
- Chuck Capacity : 13mm
- Speed of Spindle : 2,850 RPM
- Distance from Fence to Center Chisel : 76mm
- Distance from Center Chisel to Table : 152mm
- Size of Table : 185 x 290mm
- Size of Base : 196 x 287mm
- Overall Height : 680mm
- Packing Size : 635 x 330 x 385mm
- N.W./G.W. : 30/32 kgs
- CUFT : 2.0



**HIMOUNT INDUSTRIAL CO., LTD.**

7<sup>TH</sup> FL. No.325, FU HSING N. ROAD.

TAIPEI, TAIWAN, R. O. C.

TEL : 886-2-27135577 886-2-27188886

FAX : 886-2-27152218

E-Mail : [himount@himount.com](mailto:himount@himount.com)