

PRODUCT INFORMATION

FOR YOUR INQUIRIES, PLEASE
INDICATE MODEL NO., AND FOLLOWING
CATALOGUE NUMBER

STT043

Vertical Log Splitter



6 Tons



AT28640

- Generates up to 6 Tons of splitting pressure
- Splits all kinds of wood, hard or soft
- Split woods in any length between 58 and 106 cm
- Width max. diameter 40 cm
- Cylinder stroke 50 cm
- Dimensions L / W / H: 85 x 44 x 153 cm
- Large wheels and a carriage device provides mobility
- Excellent design features provide maximum safety and comfort
- An exceptional high safety standard is the two hand operating system
- Stable torsion – resistant steel construction

Optional Accessories:

Obtuse Wedge

Cross Wedge (for splitting the log 4 wood pieces at one time)

Max. 58cm



Max. 77cm



Max. 106cm



Item	Max. Wood Dia.	Wood Length (Max.) cm	Splitter Power	Power Watt	Cylinder Stoke	Cylinder Speed (Forward)	Cylinder Speed (Return)	Oil Capacity
AT28640	40 cm	58 / 77 / 106	6 Ton	3000W	50 cm	5 cm / sec.	16 cm / sec.	3.5 L

8 Tons



AT28840



- Generates up to 8 Tons of splitting pressure
- The swing-out table and safety bar facilitates the splitting of shorter logs
- Splits all kinds of wood, hard or soft
- Split woods in any length between 58 and 106 cm
- Width max. diameter 40 cm
- Cylinder stroke 53 cm
- Dimensions L / W / H: 93 x 83 x 147 cm
- Large wheels and a carriage device provides mobility
- Excellent design features provide maximum safety and comfort
- Wood holding device comes standard
- An exceptional high safety standard is the two hand operating system
- Stable torsion – resistant steel construction
- Includes splitting crossy

Optional Accessories:

Obtuse Wedge

Cross Wedge (for splitting the log 4 wood pieces at one time)

Item	Max. Wood Dia.	Wood Length (Max.) cm	Splitter Power	Power Watt	Cylinder Stoke	Cylinder Speed (Forward)	Cylinder Speed (Return)	Oil Capacity
AT28840	40 cm	58 / 77 / 106	8 Ton	3000W	53 cm	6 cm / sec.	12 cm / sec	6 L



HIMOUNT INDUSTRIAL CO., LTD.
7TH FL. No.325, FU HSING N. ROAD.
TAIPEI, TAIWAN
TEL: 886-2-27135577 886-2-27188886
FAX: 886-2-27152218
<http://www.himount.com/>
E - MAIL: info@himount.com