Quick Aluminum Bar Clamps Heavy Duty

FOR YOUR INQUIRIES, PLEASE INDICATE MODEL NO., AND FOLLOWING CATALOGUE NUMBER STV058-1

- * These aluminum bar clamps are lightweight, extremely rigid, and easy to adjust.
- * The strong extruded bars measure 1-3/8" x 7/8" for excellent resistance to bowing and twisting.
- * The bar remains reliably straight under clamping force, so you can clamp work against it to prevent misalignment.
- * Maximum opening capacity listed.
- * Clamp jaw with pad







MDOEL	BAR LENGTH	CLAMPING CAPACITY	THROAT DEPTH	NET WEIGHT (LBS / KGS)
UT0988412	24" (610mm)	18-1/2" (470mm)	3-1/2" (89mm)	1.86 LBS (0.85 KGS)
UT0988413	36" (915mm)	30-1/2" (775mm)	3-1/2" (89mm)	2.10 LBS (0.96 KGS)
UT0988414	48" (1220mm)	42-1/2" (1080mm)	3-1/2" (89mm)	2.34 LBS (1.06 KGS)
UT0988415	60" (1524mm)	54-1/2" (1384mm)	3-1/2" (89mm)	2.70 LBS (1.23 KGS)






HIMOUNT INDUSTRIAL CO., LTD. 7TH FL. No.325, FU HSING N. ROAD. TAIPEI, TAIWAN TEL: 886-2-27135577 886-2-27188886 FAX: 886-2-27152218 E - MAIL: info@himount.com http://www.himount.com

Quick Aluminum Bar Clamps

- * These aluminum bar clamps are lightweight, extremely rigid, and easy to adjust.
- * The strong extruded bars measure 1-3/8" x 7/8" for excellent resistance to bowing and twisting.
- * The bar remains reliably straight under clamping force, so you can clamp work against it to prevent misalignment.
- * Maximum opening capacity listed.







MDOEL	BAR LENGTH	CLAMPING CAPACITY	THROAT DEPTH	NET WEIGHT (LBS / KGS)
UT0988422	24" (610mm)	20" (508mm)	1-5/8" (41.3mm)	1.60 LBS (0.73 KGS)
UT0988423	36" (915mm)	32" (813mm)	1-5/8" (41.3mm)	1.98 LBS (0.90 KGS)
UT0988424	48" (1220mm)	44" (1117mm)	1-5/8" (41.3mm)	2.29 LBS (1.04 KGS)
UT0988455	60" (1524mm)	56-1/2" (1435mm)	1-5/8" (41.3mm)	2.64 LBS (1.20 KGS)





HIMOUNT INDUSTRIAL CO., LTD. 7TH FL. No.325, FU HSING N. ROAD. TAIPEI, TAIWAN TEL: 886-2-27135577 886-2-27188886 FAX: 886-2-27152218 E - MAIL: info@himount.com http://www.himount.com