

# PRODUCT INFORMATION

FOR YOUR INQUIRIES, PLEASE  
INDICATE MODEL NO., AND FOLLOWING  
CATALOGUE NUMBER

**SUT053**

## JW-215 ALUMINUM HIGH FLOW W/ P.E. HOSE PUMP



- \* Commonly used for dispensing or transferring low viscosity and non-corrosive petroleum based fluids, such as Petro, Diesel, Kerosene, Lube, Fuel, Machine Oil, etc.
- \* Counter clockwise and clockwise operation for discharging freely.
- \* Vertical conveying distance of 15 meters, horizontal conveying distance of 50 meters.
- \* Supply with 2" bung adapter and 3-piece or 40" long plated steel suction tube to fit most 15,30 and 55 gallon drums.
- \* Self-priming unit, dispenses approximately 1 liter per stroke.
- \* Do not use with organic solvents, alkalis, acids and water-based fluids.
- \* Supply with Suction Filter to filter the dirt and ensure pump life.

## JW-1461 CHROME PLATED PUMP



- \* Chrome plated steel.
- \* Commonly used for dispensing or transferring degreasers, waxes, light detergents and lubricants or equivalent which are compatible with pump component materials.
- \* Supply with 2" bung adapter and 3-piece or 40" long plated steel suction tube to fit most 15,30 and 55 gallon drums.
- \* Self-priming unit, dispenses approximately 8 oz per stroke.

## JW-300C CHROME PLATED PUMP



- \* Chrome plated steel cylinder body.
- \* Ideal for transferring non-corrosive fluids of light to medium viscosity, such as Motor Oils, Transmission Fluid, Heating Oils, Machine Oils, Automotive additives, Cleaning Solutions, Solvents, Thinner, Diesel Fuel, Kerosene, etc.
- \* Self-priming unit, dispenses approximately 22 oz per full stroke.
- \* Discharge spout can be rotated 180° and can fit I.D. 3/4" garden hose.

## JW-496T ZINC PLATED PUMP W/ HOSE & TROLLEY



- \* Suitable to be put inside 5 gallons original round barrel.
- \* Portable : to be operated manually : No electricity is needed.
- \* The base is equipped with foot-stepping stand. The operation will be even better with foot stepped on it.
- \* Suitable for all sorts of machineries, vehicles, airplanes, ships, etc. The efficient instrument with which grease can be infused powerfully for lubrication & maintenance purpose.
- \* General 00#~2# grease all can be infused into smoothly.
- \* Container is no included.

## JW-A95 AIR OPERATED OIL PUMP



- \* This Air Operated Oil Pump is applicable for greater amount of oil or gear oil transmission in short distance. Pressure ratio is 1 : 1, suitable for 0# ~ 120# oil.



**HIMOUNT INDUSTRIAL CO., LTD.**  
7TH FL. No.325, FU HSING N. ROAD.  
TAIPEI, TAIWAN, R. O. C.  
TEL: 886-2-27135577 886-2-27188886  
FAX: 886-2-27152218  
E - MAIL: himount@himount.com  
<http://www.himount.com>