

## PRODUCT INFORMATION

FOR YOUR INQUIRIES, PLEASE  
INDICATE MODEL NO., AND FOLLOWING  
CATALOGUE NUMBER

**SUT063**  
Page 1 of 2

# Hand Rotary Pump

Hand Rotary Pumps are very efficient because they naturally remove air from the lines, which are found in a wide range of applications, such as chemical-processing, liquid delivery, solvents, and auto repairing.

Maximum fluid temperature can reach to 140 ° F / 60 ° C and viscosity to 2000 SSU.

We supply with 2" bung adaptor, 3-piece suction tubes (total 1016mm) to fit most 15, 30 and 55 gallon drums.

3-piece suction tubes to save space when storage and transportation.

Make sure liquids without dirt to ensure pump life.

### UT0770A4 Polypropylene ( PP) Pump

#### Ideal for

Ad-Blue, Organic acids, Detergents, Cleaning Solutions, Soaps,  
Lubricants Based Fluids, Anti-Freeze, Organic Alcohols.

### UT0770A5 Aluminum High Flow Pump

#### Ideal for

Petrol, Diesel, Lube oils, Kerosene, Fuel oils, Machine oils

### UT0770A6 PPS (RYTON) Pump with Stainless Tube

#### Ideal for

Ad-Blue, Aggressive chemicals, Alcohols, Volatile, Acids, Soluble,  
Hydrocarbons, Corrosive, Esters, Alkali.



Item No.	Material	Max. SSU Viscosity	Capacity Per Stroke	Bung Adaptor
UT0770A4	PP, Teflon, Phenolic Resin	2000	350 ml / 12 oz	2"
UT0770A5	Aluminum, Steel, NBR and PE	500	460 ml / 16 oz	2"
UT0770A6	PPS, Stainless Steel, Teflon and NBR	2000	350 ml / 12 oz	2"



**HIMOUNT INDUSTRIAL CO., LTD.**  
7TH FL. No.325, FU HSING N. ROAD.  
TAIPEI, TAIWAN,  
TEL: 886-2-27135577 FAX : 886-2-27152218  
E - MAIL : [himount@himount.com](mailto:himount@himount.com)  
[http:// www.himount.com](http://www.himount.com)

## PRODUCT INFORMATION

FOR YOUR INQUIRIES, PLEASE  
INDICATE MODEL NO., AND FOLLOWING  
CATALOGUE NUMBER

**SUT063**  
Page 2 of 2

# Lever Action Drum Pump

Lever Action Drum Pump is one of most popular pumps around the world.

This pump saves your strength when operating.

Adjustable telescopic suction tubes length up to 890mm fits most 15, 30 and 55 gallon drums.

Maximum fluid temperature can reach to almost 140 ° F / 60 ° C.

Various materials give you multiple choices for the source of liquid.

### **UT0770B Polypropylene (PP) Pump**

#### **Ideal for**

Ad-Blue, Water, Alcohols, Lubricant, Gasoline, Kerosene, Diesel

### **UT0770B1 Stainless Steel Pump**

#### **Ideal for**

Aggressive chemicals, Alcohols, Volatile Soluble, Hydrocarbons, Corrosive, Esters, Soaps, Anti-Freeze, Water based Chemicals, Alkali, Strong Acids,

Petroleum based fluids:

Automotive Additives, Thinner, Diesel, Fuel oils, Solvents, Lube Oils

Benzene, Cleaning Solutions, Kerosene, Transmission Fluid,



### **UT0770B3 Teflon (PVDF) Pump**

#### **Ideal for**

Water, Alcohols, Lubricant, Alkaline Solutions, Gasoline, Diesel, Acid Kerosene.

Item No.	Material	Max. SSU Viscosity	Capacity Per Stroke	Bung Adaptor
<b>UT0770B</b>	PP, Steel Rod, PE, Viton	1000	400 ml / 14 oz	2" / 1-1/2"
<b>UT0770B1</b>	Stainless Steel (#304) body, PVDF (Teflon) internal parts	2000	350 ml / 12 oz	2" / 1-1/2"
<b>UT0770B3</b>	Teflon, Stainless Steel (#316) Rod	1000	400 ml / 14 oz	2" / 1-1/2"



**HIMOUNT INDUSTRIAL CO., LTD.**

7TH FL. No.325, FU HSING N. ROAD.

TAIPEI, TAIWAN,

TEL: 886-2-27135577 FAX: 886-2-27152218

E - MAIL : himount@himount.com

[http:// www.himount.com](http://www.himount.com)